

MULTI-GAS

Honeywell BW™ Max XT II

Honeywell BW™ Max XT II

Overview



Feedback

Go the distance and save with this smart, simple and economical way to compliance. **Product Overview:** Honeywell BW™ Max XT II is the smart, simple, and economical way to compliance. Workers feel safe and incidents are minimized so everyone will be able to do more. That means savings realized from business continuity and productivity. Simple operation, with SmartSample pump. Honeywell BW™ Max XT II reliably monitors up to four hazards and combines straightforward one-button operation with our robust, motorized pump for intelligent, remote sampling, ideal for confined spaces. The Honeywell BW™ Max XT II is fully compatible with MicroDock II automated test and calibration system.

Features & Benefits:

- Monitors H2S, CO, O2 and combustibles
- One-button operation with robust, motorized pump
- Compatible with MicroDock II

Quick Specs:

- Size: 5.1 x 2.8 x 2.0 in. / 13.1 x 7.0 x 5.2 cm
- Weight: 11.5 oz. / 328 g
- Temperature: -4 to 122°F / -20 to 50°C
- Readily enables to communicate with Motorola MOTOTRBO

Even the best products deserve expert maintenance!

Elevate your gas detectors' potential with Honeywell's expert maintenance services! Maximize uptime, eliminate costs, and ensure on-time, on-budget project completion.

Specifications

BRAND

Brand

- BW
- Honeywell BW

DIMENSION & WEIGHT

Weight

- 11.5 ounce av
- 328 gram

Instrument Size

- 5.1 x 2.8 x 2.0 in. / 13.1 x 7.0 x 5.2 cm

Weight range

- 328 g gram

CATEGORY

Sub-Category

- Multi-Gas
- Multi-Gas Detector

RANGE

Humidity Range

- 10 to 100% RH (Non-Condensing) percent
- 10%-100% percent

Sensor Range

- CO: 0-1,000 ppm
- H2S: 0-200 ppm
- LEL: 0-100% and 0-5.0% v/v
- O2: 0 to 30.0%

TEMPERATURE

Minimum Temperature

- -20
- -20 degree Celsius
- -4 degree Fahrenheit

Maximum Temperature

- 122 degree Fahrenheit
- 50
- 50 degree Celsius

ALARM

Alarm Settings

- Low, High, STEL, TWA, OL (Over Limit), Low Battery, Pump

Alarm Type

- Audible (95 dB)
- Vibrating
- Visual

FEATURES

Alarm Included

- Yes

Series Name

- HoneywellBW MaxXT II

Languages

- English, French, German, Spanish, Portuguese

BATTERY & CHARGING

Batteries Required

- Yes

Batteries Included

- Yes

Battery Run Time

- 13 Hours hours
- 8 Hours @-20°C hours
- 8-13 hours

Charging Time

- 6 hours

CERTIFICATIONS

Standards

- ATEX: X g II 1 G Ga Ex ia IIC T4
- BR-Exia IIC T4
- IECEX: Ga Ex ia IIC T4
- UL: Class I, Div 1, Group A, B, C, D

DATALOGGING

Datalogging Capable

- Yes

Datalogging

- 375 hours at 15-second intervals
- Standard Datalogging and Event Logging

Feedback

Display Included

- Yes

Display Readout

- Low, High, STEL, TWA, OL (Over Limit), Low Battery, Pump

Display Type

- LCD

FEATURES & BENEFITS

Features & Benefits

- Best in Class Block Detection with Semi-Conductor Pressure Sensor
- Bright Wide-Angled Visual Alarm Bars
- Built-In Concussion Proof Boot
- Compact and Lightweight Design Makes It Comfortable to Wear
- Continuous LCD Shows Real-Time Gas Concentrations
- Continuous Visual Compliance with IntelliFlash™
- Conveniently Manage Your Detector with Fleet Manager II
- Equipped with Standard Datalogging and Event Logging
- Integrated Sampling Pump with Reliable Diaphragm Technology
- Multi-Language Support in English, French, German, Spanish and Portuguese

FILTER

Filter Included

- Yes

OPTIONS

User Options

- Calibration IR Lock
- Confidence Beep
- Confidence Interval
- Datalog Interval
- Detector Identification
- Force Block Test
- Force Bump Test when Overdue
- Force Calibration when Overdue
- Language Choices (Five)
- Latching Alarms
- Location Selection
- Low Alarm Acknowledge
- Safe Display Mode
- Safety (Sensor) Lock
- Sensor Configuration
- Set Custom Start Up Message

SAMPLING

Sampling Pump Included

- Yes

Sampling Pump Range

- 75 ft meter
- 75ft (23m) meter

SENSOR

Number of Sensors Included

- 4

Sensor Type

- Semi-Conductor Pressure Sensor

SHELF LIFE

Operating Life

- 2 years

WARRANTY

Warranty

- 2 Years Including All Sensors
- Full two year warranty including all sensors

WIRELESS

Wireless Technology

- BLE

ADDITIONAL SPECIFICATIONS

Combustible Concentration

- 0-100% LEL, 0-5.0% v/v

External Calibration

- MicroCock II Automated Test and Calibration System

Combustible

- Yes

Gas Type

- H2S, CO, O2, LEL

Decibels

- 95 decibel

STANDARDS & CERTIFICATIONS

Ingress Protection

- IP66/67
- IP66/67

DIMENSIONS & WEIGHT

Size

- H: 5.1 in W: 2.8 in D: 2.0 in

TECHNICAL SPECIFICATIONS

Gases Detected

- H2S, CO, O2, LEL

Sensor Life

- 2 Years

Keypad Type

- One Button Operation

Attachment

- Concussion-Proof Boot
- Honeywell BW Connect
- MicroDock II Compatible
- Multi-Unit Cradle Charger

Pump Draw

- Sample from up to 75 ft / 23m

Sampling

- Integrated Sampling Pump with Reliable Diaphragm Technology

EMC/RFI

- EMC Directive: 2004/108/EC

Tests

- Audible/Visual Alarms on Activation, Sensors, Battery, Pump and Circuitry (Continuous)

ELECTRICAL SPECIFICATIONS

Power Source

- Battery



Please sign in to view part numbers available for purchase based on your account

Sign In

Search

Part Number	115390-L3
Description	Particulate pump filter (thin) replacement (kit of 100) SIGN IN
Part Number	126561-L3
Description	GASALERTMAX XT O2 LEL H2S CO NA SIGN IN
Part Number	126727-L3
Description	GASALERTMAX XT O2 LEL H2S CO EU

Feedback

SIGN IN	
Part Number	126728-L3
Description	GASALERTMAX XT O2 LEL H2S CO UK SIGN IN
Part Number	126736-L3
Description	GASALERTMAX XT O2 LEL H2S CO EU SIGN IN
Part Number	126737-L3
Description	GASALERTMAX XT O2 LEL H2S CO UK SIGN IN
Part Number	126751-L3
Description	Carrying holster for BW Max XT II and sampling hose SIGN IN
Part Number	126826-L3
Description	Carrying Case For Gasalertmax Xt (With SIGN IN
Part Number	126829-L3
Description	BW Max XT II Deluxe Confined Space Kit Detector and calibration gas sold separately. SIGN IN
Part Number	126831-L3
Description	Multi Unit Cradlecharger (5) For Max Xt SIGN IN

Feedback

Product Number

Please sign in to view part numbers available for purchase based on your account

Sign In

115390-L3
Particulate pump filter (thin) replacement (kit of 100)

115390-L3
Particulate pump filter (thin) replacement (kit of 100)

126561-L3
GASALERTMAX XT O2 LEL H2S CO NA

126561-L3
GASALERTMAX XT O2 LEL H2S CO NA

126727-L3
GASALERTMAX XT O2 LEL H2S CO EU

GASALERTMAX XT O2 LEL H2S CO EU

126727-L3

GASALERTMAX XT O2 LEL H2S CO EU

126728-L3

GASALERTMAX XT O2 LEL H2S CO UK

126728-L3

GASALERTMAX XT O2 LEL H2S CO UK

126729-L3

GASALERTMAX XT O2 LEL H2S CO AU

126729-L3

GASALERTMAX XT O2 LEL H2S CO AU

126736-L3

GASALERTMAX XT O2 LEL H2S CO EU

126736-L3

GASALERTMAX XT O2 LEL H2S CO EU

126737-L3

GASALERTMAX XT O2 LEL H2S CO UK

126737-L3

GASALERTMAX XT O2 LEL H2S CO UK

126738-L3

GASALERTMAX XT O2 LEL H2S CO AU

126738-L3

GASALERTMAX XT O2 LEL H2S CO AU

126751-L3

Carrying holster for BW Max XT II and sampling hose

126751-L3

Carrying holster for BW Max XT II and sampling hose

126826-L3

Carrying Case For Gasalertmax Xt (With

126826-L3

Carrying Case For Gasalertmax Xt (With

Alternative Products



QRAE 3

Versatile Compact wireless monitor for up to four gases



Honeywell BW™ Ultra

Honeywell BW™ Ultra

Feedback

Honeywell
Industrial Automation
855 S Mint St
Charlotte, NC 28202
800-582-4263

Product name
© Current year Honeywell International Inc.
All rights reserved.

Honeywell

This document was generated on (YYYY-MM-DD, HH:mm:ss). Subject to change without notice.

Fire Hunter Co
Also known as Sayaad Alnaar Company
29a street ,Naif road ,UAE
Admin@firehunter.co
00971543370006

**Fire
Hunter**