

Adjustable flow rate and stream patterns hand nozzles



The 500 lpm adjustable flow rate and stream patterns hand nozzles are available in two versions. "ECO" and "Premium". The calibrated flow rates are easily selectable by means of an indexed ring. The tactile marker indicates the highest flow rate. The indexed head ring with tactile markings allows the adjustment of the different stream patterns (straight spray, attack spray and wide angle spray). This range of nozzles is available with three different head types : Turbo (spinning teeth), Debi (cut teeth) and Magi (molded rubber teeth). These nozzles are used by a large number of firefighters all around the world.

Maximum working pressure: PN16
Shutoff: ball valve
Opening: by operating handle
Flush position: yes
Material: aluminium alloy
Surface treatment: hard anodisation
Body type : profile
Pistol grip : single


Options: low expansion foam attachment, medium expansion foam attachment.

Sheath colours:

**Compliant with the norm
EN 15182-2**




MAGIKADOR 500



Inlet	Flow rate	Working pressure	Dimensions (mm)	Weight (kg)	Ref.
1.5" female NST-NH	30-60-95 GPM	100 PSI	290 x 126 x 266	2.4	18458
1.5" female NST-NH	30-60-95-125 GPM	100 PSI	290 x 126 x 266	2.4	18459
1.5" female NST-NH	40-60-95-125 GPM	100 PSI	290 x 126 x 266	2.4	18486
1.5" female NST-NH	60-95-125 GPM	100 PSI	290 x 126 x 266	2.4	18487
DSP DN40	150-250-500 lpm	6 bar	312 x 126 x 266	2.5	22969
DSP DN40	150-250 lpm	6 bar	312 x 126 x 266	2.5	28611.DSP40
DSP DN40	60-120-180-240 lpm	6 bar	312 x 126 x 266	2.5	28639
DSP DN40	60-130-235 lpm	6 bar	312 x 126 x 266	2.5	28621
DSP DN40	200-350-500 lpm	6 bar	312 x 126 x 266	2.5	28633
DSP DN40	150-250-350-500 lpm	6 bar	312 x 126 x 266	2.5	28645

Compatible with the low expansion ref. 09297 and medium expansion ref. 09713 foam attachments


DEBIKADOR 500



Inlet	Flow rate	Working pressure	Dimensions (mm)	Weight (kg)	Ref.
1.5" female NST-NH	30-60-95 GPM	100 PSI	290 x 126 x 266	2.4	13720
1.5" female NST-NH	60-95-125 GPM	100 PSI	290 x 126 x 266	2.4	13721
1.5" female NST-NH	30-60-95-125 GPM	100 PSI	290 x 126 x 266	2.4	13722
1.5" female NST-NH	40-60-95-125 GPM	100 PSI	290 x 126 x 266	2.4	18485
DSP DN40	150-250 lpm	6 bar	312 x 126 x 266	2.5	18992
DSP DN40	150-250-500 lpm	6 bar	312 x 126 x 266	2.5	22466.DSP40
DSP DN40	60-130-235 lpm	6 bar	312 x 126 x 266	2.5	28623
DSP DN40	200-350-500 lpm	6 bar	312 x 126 x 266	2.5	28635
DSP DN40	150-250-350-500 lpm	6 bar	312 x 126 x 266	2.5	28647

Compatible with the low expansion ref. 09297 and medium expansion ref. 09713 foam attachments

TURBOKADOR 500



Inlet	Flow rate	Working pressure	Dimensions (mm)	Weight (kg)	Ref.
1.5" female NST-NH	40-60-95-125 GPM	100 PSI	290 x 126 x 266	2.4	08349
1.5" female NST-NH	30-60-95-125 GPM	100 PSI	290 x 126 x 266	2.4	08370
1.5" female NST-NH	30-60-95 GPM	100 PSI	290 x 126 x 266	2.4	09891
1.5" female NST-NH	60-95-125 GPM	100 PSI	290 x 126 x 266	2.4	09892
DSP DN40	100-200-300 lpm	6 bar	312 x 126 x 266	2.5	16219
DSP DN40	150-250 lpm	6 bar	312 x 126 x 266	2.5	16640
DSP DN40	150-250-500 lpm	6 bar	312 x 126 x 266	2.5	25217
DSP DN40	150-500 lpm	6 bar	312 x 126 x 266	2.5	28619
DSP DN40	200-350-500 lpm	6 bar	312 x 126 x 266	2.5	28637
DSP DN40	60-120-180-240 lpm	6 bar	312 x 126 x 266	2.5	28643
DSP DN40	150-250-350-500 lpm	6 bar	312 x 126 x 266	2.5	28649

Compatible with the low expansion ref. 09297 and medium expansion ref. 09713 foam attachments