

Adjustable flow rate and stream patterns hand nozzles



The 750 lpm adjustable flow rate and stream patterns hand nozzles represent the ideal compromise between the 500 lpm and 1000 lpm versions. They offer power, lightness, and manoeuvrability. The nozzles are available in two versions: "ECO" and "Premium". The calibrated flow rates are easily selectable by means of an indexed ring. The tactile marker indicates the highest flow rate. The head ring with tactile markings allows different spray pattern selection (straight spray, flash over and wide angle spray). This range of nozzles is available with three different head types: Debi (cut teeth), Magi (molded rubber teeth) and Turbo (spinning teeth).

Maximum working pressure: PN16
Shutoff: ball valve
Opening: by operating handle
Flush position: yes
Material: aluminium alloy
Surface treatment: hard anodisation
Body type: molded
Pistol grip: single


Options: low expansion foam attachment, medium expansion foam attachment.

Sheath colours:

**Compliant with the norm
EN 15182-2**




MAGIKADOR 750 - ECO



Inlet	Flow rate	Working pressure	Dimensions (mm)	Weight (kg)	Ref.
DSP DN65	250-500-750 lpm	6 bar	422 x 126 x 260	4.1	44271
DSP DN65	350-500-600-750 lpm	6 bar			44272
2.5" female NST-NH	125-180 GPM	100 PSI	416 x 126 x 260	4.1	44273
2.5" female NST-NH	95-125-150-200 GPM	100 PSI			44274

Compatible with the low expansion ref. 27487 and medium expansion ref. 44308 foam attachments


DEBIKADOR 750 - ECO



Inlet	Flow rate	Working pressure	Dimensions (mm)	Weight (kg)	Ref.
DSP DN65	250-500-750 lpm	6 bar	416 x 126 x 260	4.1	44275
DSP DN65	350-500-600-750 lpm	6 bar			44276
2.5" female NST-NH	125-180 GPM	100 PSI	417 x 126 x 260	4.1	44277
2.5" female NST-NH	95-125-150-200 GPM	100 PSI			44278

Compatible with the low expansion ref. 27487 and medium expansion ref. 44308 foam attachments

Turbokador 750 - ECO



Inlet	Flow rate	Working pressure	Dimensions (mm)	Weight (kg)	Ref.
DSP DN65	350-500-600-750 lpm	6 bar	417 x 126 x 260	4.1	44348
DSP DN65	250-500-750 lpm	6 bar	417 x 126 x 260	4.1	44347
2.5" female NST-NH	125-180 GPM	100 PSI	417 x 126 x 260	4.1	44349
2.5" female NST-NH	95-125-150-200 GPM	100 PSI			44350

Compatible with the low expansion ref. 27487 and medium expansion ref. 44308 foam attachments